

SOUND RETARDANT DOOR
Sound Transmission class (STC) 39
Formaldehyde Free

OSHKOSH
Door Company

GFA39

CARB (California Air Resources Board) compliant

SPECIFICATIONS

Industry Performance Standards

WDMA IS.1.A11 & AWS -09

(also older versions of WDMA, AWI 1300 and WI section 20 when specified)

Maximum sizes

3-0 X 7-0 single

Thickness

1 3/4"

Core

Special acoustical materials IEQ 4.4 (no added formaldehyde)

Stiles

Matching veneer or HPL over composite fire rated material

Top & Bottom Rails

Fire retardant composite

Core Assembly

Stiles and rails bonded to core

Face Assembly / Adhesive

Faces & crossbands hot-pressed to core with Type I glue

Crossband

Engineered wood product

Faces

Domestic and exotic veneer species, medium density overlay or .050 HPL

Labeling

45 Min. singles doors. Subject to ASTM E-152 and Intertek Testing Service (Warnock Hersey) Positive Pressure Category "A"

Special Details

Available with vision kits up to 100 square inches
Check with factory for machining options

Factory Finish

UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.

Vision Kit

100 sq. in. of 19mm pyrostop

Acoustic Rating

STC39 (operable unit) When installed with appropriate gasketing

Gasketing

Set 19: See detail drawing sheet **DD619** for gaskets and installation

Warranty

Full Door Warranty for Life of Installation on interior applications.
Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.

Visit us at www.oshkoshdoor.com

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

OSHKOSH
Door Company

For more information call: **920-233-6161**

Date: 8/13

Product Data Sheet: 623