

SOUND RETARDANT DOOR

Sound Transmission Class (STC) 35

OSHKOSH
Door Company

GFA35-12

CARB (California Air Resources Board) compliant

SPECIFICATIONS

Industry Performance Standards

WDMA IS.1.A11 & AWS -09

(also older versions of WDMA, AWI 1300 and WI section 20 when specified)

Maximum sizes

4-0 X 9-0 single

Thickness

1 3/4"

Core

Special acoustical materials

Stiles

Matching veneer or HPL over composite fire rated material

Top & Bottom Rails

Mill option hardwood or SCL (structural composite lumber)

Core Assembly

Stiles and rails bonded to core

Face Assembly / Adhesive

Faces & crossbands hot-pressed to core with Type I glue

Crossband

Engineered wood product

Faces

Domestic and exotic veneer species, medium density overlay or .050 HPL

Labeling

45 - 90 Min. singles doors. Subject to ASTM E-152 and Intertek Testing Service (Warnock Hersey) Positive Pressure Category "A"

Special Details

Check with factory for machining options

Factory Finish

UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.

Acoustic Rating

STC35 (operable unit) When installed with appropriate gasketing

Gasketing

Set12: See detail drawing sheet **DD612A** for gaskets and installation of

Warranty

Full Door Warranty for Life of Installation on interior applications. *Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.*

Visit us at www.oshkoshdoor.com

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

OSHKOSH
Door Company

For more information call: **920-233-6161**

Date: 6/12

Product Data Sheet: 612A