

# SOUND RETARDANT DOOR

Sound Transmission Class (STC) 35

**OSHKOSH**  
Door Company

**GFA35-6**

CARB (California Air Resources Board) compliant

## SPECIFICATIONS

<b>Industry Performance Standards</b>	<b>WDMA IS.1.A11 &amp; AWS -09</b> (also older versions of WDMA, AWI 1300 and WI section 20 when specified)
<b>Maximum sizes</b>	4-0 X 9-0 single
<b>Thickness</b>	1 3/4"
<b>Core</b>	Special acoustical materials
<b>Stiles</b>	Matching veneer or HPL over composite fire rated material
<b>Top &amp; Bottom Rails</b>	Mill option hardwood or SCL (structural composite lumber)
<b>Core Assembly</b>	Stiles and rails bonded to core
<b>Face Assembly / Adhesive</b>	Faces & crossbands hot-pressed to core with Type I glue
<b>Crossband</b>	Engineered wood product
<b>Faces</b>	Domestic and exotic veneer species, medium density overlay or .050 HPL
<b>Labeling</b>	45 - 90 Min. singles doors. Subject to ASTM E-152 and Intertek Testing Service (Warnock Hersey) Positive Pressure Category "A"
<b>Special Details</b>	Check with factory for machining options
<b>Factory Finish</b>	UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.
<b>Acoustic Rating</b>	STC35 (operable unit) When installed with appropriate gasketing
<b>Gasketing</b>	<b>Set 6:</b> See detail drawing sheet <b>DD612</b> for gaskets and installation of
<b>Warranty</b>	Full Door Warranty for Life of Installation on interior applications. <i>Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.</i>

**Visit us at [www.oshkoshdoor.com](http://www.oshkoshdoor.com)**

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

**OSHKOSH**  
Door Company

For more information call: **920-233-6161**

Date: 6/12

Product Data Sheet: 612