

# SOUND RETARDANT DOOR

## Sound Transmission Class (STC) 37

**OSHKOSH**  
Door Company

**GFA37-9**

CARB (California Air Resources Board) compliant

### SPECIFICATIONS

#### Industry Performance Standards

#### WDMA IS.1.A11 & AWS -09

(also older versions of WDMA, AWI 1300 and WI section 20 when specified)

#### Maximum sizes

3-0 X 7-0 single

#### Thickness

1 3/4"

#### Core

Special acoustical materials

#### Stiles

Matching veneer or HPL over composite fire rated material

#### Top & Bottom Rails

Mill option hardwood or SCL (structural composite lumber)

#### Core Assembly

Stiles and rails bonded to core

#### Face Assembly / Adhesive

Faces & crossbands hot-pressed to core with Type I glue

#### Crossband

Engineered wood product

#### Faces

Domestic and exotic veneer species, medium density overlay or .050 HPL

#### Labeling

45 Min. singles doors. Subject to ASTM E-152 and Intertek Testing Service (Warnock Hersey) Positive Pressure Category "A"

#### Special Details

Available with vision kits up to 100 square inches  
Check with factory for machining options

#### Factory Finish

UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.

#### Acoustic Rating

STC37 (operable unit) When installed with appropriate gasketing

#### Gasketing

**Set 9:** See detail drawing sheet **DD610** for gaskets and installation of

#### Warranty

Full Door Warranty for Life of Installation on interior applications.  
*Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.*

**Visit us at [www.oshkoshdoor.com](http://www.oshkoshdoor.com)**

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

**OSHKOSH**  
Door Company

For more information call: **920-233-6161**

Date: 6/12

Product Data Sheet: 610