

SOUND RETARDANT DOOR

Sound Transmission Class (STC) 38

OSHKOSH
Door Company

GFA38-8

CARB (California Air Resources Board) compliant

SPECIFICATIONS

Industry Performance Standards

WDMA IS.1.A11 & AWS -09

(also older versions of WDMA, AWI 1300 and WI section 20 when specified)

Maximum sizes

4-0 x 8-0 single

Thickness

1 3/4"

Core

Special acoustical materials

Stiles

Matching veneer or HPL over composite fire rated material

Top & Bottom Rails

Mill option hardwood or SCL (structural composite lumber)

Core Assembly

Stiles and rails bonded to core

Face Assembly / Adhesive

Faces & crossbands hot-pressed to core with Type I glue

Crossband

Engineered wood product

Faces

Domestic and exotic veneer species, medium density overlay or .050 HPL

Labeling

45 and 60 Min. singles doors. Subject to ASTM E-152 and Intertek Testing Service (Warnock Hersey) Positive Pressure Category "A"

Special Details

Check with factory for machining options

Factory Finish

UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.

Acoustic Rating

STC38 (operable unit) When installed with appropriate gasketing

Gasketing

Set 8: See detail drawing sheet **DD609** for gaskets and installation of

Warranty

Full Door Warranty for Life of Installation on interior applications.
Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.

Visit us at www.oshkoshdoor.com

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

OSHKOSH
Door Company

For more information call: **920-233-6161**

Date: 6/12

Product Data Sheet: 609