

SOUND RETARDANT DOOR

Sound Transmission Class (STC) 39

OSHKOSH
Door Company

GFA39-1

CARB (California Air Resources Board) compliant

SPECIFICATIONS

Industry Performance Standards	WDMA IS.1.A11 & AWS -09 (also older versions of WDMA, AWI 1300 and WI section 20 when specified)
Maximum sizes	3-0 X 7-0 single
Thickness	1 3/4"
Core	Special acoustical materials
Stiles	Matching veneer or HPL over composite fire rated material
Top & Bottom Rails	Mill option hardwood or SCL (structural composite lumber)
Core Assembly	Stiles and rails bonded to core
Face Assembly / Adhesive	Faces & crossbands hot-pressed to core with Type I glue
Crossband	Engineered wood product
Faces	Domestic and exotic veneer species, medium density overlay or .050 HPL
Labeling	45 Min. singles doors. Subject to ASTM E-152 and Intertek Testing Service (Warnock Hersey) Positive Pressure Category "A"
Special Details	Available with vision kits up to 100 square inches Check with factory for machining options
Factory Finish	UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.
Acoustic Rating	STC39 (operable unit) When installed with appropriate gasketing
Gasketing	Set 1: See detail drawing sheet DD607 for gaskets and installation of
Warranty	Full Door Warranty for Life of Installation on interior applications. <i>Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.</i>

Visit us at www.oshkoshdoor.com

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

OSHKOSH
Door Company

For more information call: **920-233-6161**

Date: 6/12

Product Data Sheet: 607