

5 PLY PARTICLE CORE 45 MINUTE

EXTRA HEAVY DUTY*

***No Additional Blocking Required**

CARB (California Air Resources Board) compliant

OSHKOSH
Door Company

GFP45

SPECIFICATIONS

Industry Performance Standards

WDMA IS.1.A-04 & AWS -09
(also older versions of AWI 1300 and WI section 20 when specified)

Maximum sizes

4-0 X 8-0 single and 6-0 X 7-0 std pairs (no Dble Egress)

Thickness

1 3/4"

Core

Particle core complies with ANSI A208.1 (38 lb.)
Core is **LEED compliant to MR 4** (Recycled content)

Stiles

Matching veneer or HPL over composite fire rated material

Top & Bottom Rails

Composite fire rated material

Core Assembly

Stiles and rails bonded to core

Face Assembly / Adhesive

Faces & crossbands hot-pressed to core with Type I glue

Crossband

Engineered wood product

Faces

Domestic and exotic veneer species, medium density overlay or .050 HPL

Labeling

45 Min. 1 3/4" thick doors. Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure

Special Details

Machining for templated hardware, lights, louvers and applied moldings.
Refer to specific technical sheets for details and limitations.

Factory Finish

UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.

Warranty

Full Door Warranty for Life of Installation on interior applications.
Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.

Visit us at www.oshkoshdoor.com

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

OSHKOSH
Door Company

For more information call: **920-233-6161**

Date: 7/11

Product Data Sheet: 201