

Extra Heavy Duty*	* No Additional Blocking Required
	CARB (California Air Resources Board) compliant
Industry Performance Standards	WDMA IS.1.A-04 & AWS -09 (also older versions of AWI 1300 and WI section 20 when specified)
Maximum Sizes	4-0 X 8-0 single and 6-0 X 7-0 std pairs (no Dble Egress)
Thickness	1 3/4"
Core	Particle core complies with ANSI A208.1 (38 lb.) Core is LEED compliant to MR 4 (Recycled content)
Stiles	Matching veneer or HPL over composite fire rated material
Top & Bottom Rails	Composite fire rated material
Core Assembly	Stiles and rails bonded to core
Face Assembly / Adhesive	Faces & crossbands hot-pressed to core with Type I glue
Crossband	Engineered wood product
Faces	Domestic and exotic veneer species, medium density overlay or .050 HPL
Labeling	45 Min. 1 3/4" thick doors. Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
Special Details	Machining for templated hardware, lights, louvers and applied moldings. Refer to specific technical sheets for details and limitations.
Factory Finish	UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.
Warranty	Full Door Warranty for Life of Installation on interior applications. <i>Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.</i>

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.