

Extra Heavy Duty*	* No additional blocking required	
	CARB (California Air Resources Board) Compliant	
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 – 2014 (also older version of WDMA, AWI 1300 and WI Section 20 when specified)	
Thickness	1-3/4"	
Maximum Sizes	Single 4 ⁰ x 10 ⁰	Single with 20 minute label 4 ⁰ x 8 ⁰
Core & STC Rating	Bullet resistant materials tested and labeled per UL 752 Core contains no added formaldehyde and is LEED compliant with EQ credit 4.4	
Bullet Resistant Ratings	Available in resistance levels 1, 2, and 3 (per UL 752)	
Stiles	Bullet resistant material covered with veneer of HPL to match face	
Rails	Bullet resistant material	
Faces	Domestic & exotic veneer species, medium density overlay or .050 HPL	
Core Assembly	Stiles & rails securely bonded to core	
Face Assembly Adhesive	Faces & crossbands (engineered wood product) hot-pressed to core with Type I glue	
Warranty	Interior Use —Life of installation * See complete warranty for details.	High Gloss Finish/ Exterior Use —No Warranty
Labeling	20 Minute Rating (4⁰ x 8⁰) Subject to ASTM E-152	Positive Pressure Category B
Special Details	Allowed hardware: butt or continuous hinges, cylindrical and mortise locks use of other hardware may affect the bullet resistance resulting in a construction only label.	
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching available > Priming for field painting	
Acoustic Rating	STC 31 (operable unit) when installed with appropriate gasketing 1-3/4" only	
LEED® v3 Credit Assistance	EQ 4.4 Low Emitting Materials	

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.