

## GF 5-Ply Mineral Core No Added Urea Formaldehyde (NAUF)



CARB (California Air Resources Board) Compliant	
<b>Industry Performance Standards</b>	WDMA IS.1.A13 & AWS Edition 2 – 2014 (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
<b>Thickness</b>	1-3/4"
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 10 <sup>0</sup> Pairs 8 <sup>0</sup> x 10 <sup>0</sup> (regular or 8 <sup>0</sup> X 8 <sup>0</sup> DE pair)
<b>Core &amp; STC Rating</b>	Non-combustible, asbestos free, <b>NAUF mineral core</b> Core is <b>LEED Compliant with EQ Credit 4.4</b>
<b>Stiles</b>	Matching veneer or HPL over composite fire rated mineral
<b>Rails</b>	Composite fire rated mineral Optional: Oversized rails available
<b>Faces</b>	Domestic & exotic veneer species, medium density overlay or .050 HPL
<b>Core Assembly</b>	Stiles & rails securely bonded to core using our state of the art hot press technology.
<b>Face Assembly Adhesive</b>	Faces & crossbands hot-pressed to core with Type I glue
<b>Warranty</b>	<b>Interior Use</b> —Life of installation <b>High Gloss Finish/ Exterior Use</b> —No Warranty * See complete warranty for details.
<b>Labeling</b>	<b>45, 60, &amp; 90 Minute Rating in singles and pairs.</b> Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
<b>Special Details</b>	Machining for template hardware, lights, louvers, Dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear      > Standard color selections > Custom color matching available      > Priming for field painting
<b>LEED® v3 Credit Assistance</b>	<b>EQ 4.4 Low Emitting Materials</b>

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.