

GFPF45

5-Ply Par	ticleboard Core
45 Minut	e
No Adde	d Urea-Formaldehyde (NAUF)



Extra Heavy Duty*	* No Additional Blocking Required
	CARB (California Air Resources Board) Compliant
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 – 2014 (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
Thickness	1-34"
Maximum Sizes	Single 4° x 8° Standard Pairs 6° x 7° (no double egress)
Core	Complies with the ANSI A 208.1, Grade LD-2 specification (38 lbs.) Core is LEED compliant for MR 4 and EQ 4.4 (NAUF).
Stiles	Matching veneer or HPL over composite fire rated material
Rails	Composite fire rated material
Faces	Domestic & exotic veneer species, medium density overlay or .050 HPL
Core Assembly	Stiles & rails securely bonded to core using our state of the art hot press technology.
Face Assembly Adhesive	Faces & crossbands (engineered wood product) hot-pressed to core with Type I glue.
Warranty	Interior Use—Life of installation High Gloss Finish/ Exterior Use—No Warranty * See complete warranty for details.
Labeling	45 Minute Rating: 1-¾" thick doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure.
Special Details	Machining for template hardware, lights, & applied moldings. Refer to specific technical sheets for details and limitations.
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Custom color matching available > Priming for field painting
Acoustic Rating	STC 31 (operable unit) when installed with appropriate gasketing 1-3/4" only
LEED® v3 Credit Assistance	MR 4 Recycled Content—Entire assembly 85% pre-consumer, 0% post-consumer. Core 100% pre-consumer, 0% post-consumer EQ 4.4 Low Emitting Material Content

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.