

**GFPFSC35**  
**5-Ply FSC® Certified**  
**Particleboard Core 45 Minute**  
**No Added Urea-Formaldehyde (NAUF)**



<b>Extra Heavy Duty*</b>		<b>* No Additional Blocking Required</b>	
		<b>CARB (California Air Resources Board) Compliant</b>	
<b>Industry Performance Standards</b>	<b>WDMA IS.1.A13 &amp; AWS Edition 2 – 2014</b> (also older version of WDMA, AWI 1300 and WI Section 20 when specified)		
<b>Thickness</b>	1-3/4"		
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 8 <sup>0</sup>	Standard Pairs 6 <sup>0</sup> x 7 <sup>0</sup> (no double egress)	
<b>Core</b>	100% <b>FSC® Certified NAUF Particleboard Core</b> with chain of custody certification (38 lbs.) Core is <b>LEED compliant for MR 4, MR 7, and EQ 4.4 (NAUF).</b>		
<b>Stiles</b>	Matching veneer or HPL over composite fire rated material		
<b>Rails</b>	Composite fire rated material		
<b>Faces</b>	Domestic & exotic veneer species, medium density overlay or .050 HPL		
<b>Core Assembly</b>	Stiles & rails securely bonded to core using our state of the art hot press technology.		
<b>Face Assembly Adhesive</b>	Faces & crossbands (engineered wood product) hot-pressed to core with Type I glue.		
<b>Warranty</b>	<b>Interior Use</b> —Life of installation		<b>High Gloss Finish/ Exterior Use</b> —No Warranty * See complete warranty for details.
<b>Labeling</b>	<b>45 Minute Rating:</b> 1-3/4" thick doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure.		
<b>Special Details</b>	Machining for template hardware, lights, & applied moldings. Refer to specific technical sheets for details and limitations.		
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)		> Standard color selections > Priming for field painting
	> Clear		> Custom color matching available
<b>Acoustic Rating</b>	STC 31 (operable unit) when installed with appropriate gasketing 1-3/4" only		
<b>LEED® v3 Credit Assistance</b>	<b>MR 4 Recycled Content</b> —Entire assembly 85% pre-consumer, 0% post-consumer. Core 100% pre-consumer, 0% post-consumer <b>MR 7 Certified Wood</b> > FSC® Certification # SCS-COC-004714 > FSC® License # FSC-C020145 <b>EQ 4.4 Low Emitting Material Content</b>		

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.