



Solutions for Today. Impressions for Life.

GLL
Lead Lined -- Optional constructions can comply with
FSC® Certified
or No Added Urea-Formaldehyde (NAUF)

CARB (California Air Resources Board) Compliant	
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 – 2014 (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
Thickness	1-3/4"
Maximum Sizes	Single 4 ⁰ x 10 ⁰ Pairs 8 ⁰ x 8 ⁰ (not rated) Single 4 ⁰ X 8 ⁰ Pairs 8 ⁰ X 8 ⁰ (20, 45, and 60 minute rated)
Core	Particleboard core (LSL available for additional charge) non-rated and 20 minute doors. 100% FSC® Certified NAUF Particleboard Core with chain of custody certification. Core can be LEED compliant for MR 7, and EQ 4.4 (NAUF) . Fire rated composite material for 45 and 60-minute doors.
Stiles	Matching veneer or HPL over mill option hardwood or composite stiles
Lead	1/32" to 1/8"
Rails	Structural Composite Lumber Composite fire rated material at 45 or 60 minute
Faces	Domestic & exotic veneer species, medium density overlay or .050 HPL
Core Assembly	Stiles & rails securely bonded to core using our state of the art hot press technology.
Face Assembly Adhesive	Faces & crossbands (engineered wood product) hot-pressed to core with Type II or Type I glue.
Warranty	Interior Use —Life of installation High Gloss Finish/ Exterior Use —No Warranty * See complete warranty for details.
Labeling	20, 45, and 60 Minute Rating Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure.
Special Details	Machining for templated hardware, lights, and applied moldings. Refer to specific technical sheets for details and limitations.
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching available > Priming for field painting
LEED® v3 Credit Assistance	MR 7 Certified Wood > FSC® Certification # SCS-COC-004714 > FSC® License # FSC-C020145 EQ 4.4 Low Emitting Material Content

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.