OSHKOSH
Door Company
Right product. Right place. Right time.

GP
5-Ply Particleboard Core

Standard Duty* *(unblocked)*	*** Heavy Duty or Extra Heavy Duty with Blocking**
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1
Thickness	1-¾", 2", 2-¼" • 1-$^{3}/_{8}$" (max size 1-$^{3}/_{8}$" 3^0 X 7^0 & 6^0 X 7^0 pair)
Maximum Sizes	Single 4^0 x 10^0 Pairs 8^0 x 10^0 (regular or DE pair)
Core	Particleboard complies with ANSI A208.1 grade 1 – LD- 2 (33 lb.)
Stiles	Matching veneer, HPL or PVC over Structural Composite Lumber (SCL), optional solid wood stiles available
Rails	Structural Composite Lumber (SCL), optional oversized rails available
Faces	Domestic & exotic veneer species, medium density overlay or HPL
Crossband	Engineered wood product
Core Assembly	Stiles & rails securely bonded to core
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue
Warranty	Interior Use - Life of installation High Gloss Finish/ Exterior Use - No Warranty *See complete warranty for details.
Labeling	20 Minute Rating: 1-¾" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
Special Details	Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) • Clear • Standard color selections • Custom color matching available • Priming for field painting
Acoustic Rating	STC 31 (operable unit) when installed with appropriate gasketing, 1-¾" only
Sustainability	• LEED v3 Credit: MR 4 Recycled Content (core 46% pre-consumer, 0% post-consumer) • LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material and Acoustic Performance • CARB (California Air Resources Board) compliant, ULEF • TSCA Title VI compliant • Greenguard and Greenguard Gold certification

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

Oshkosh, Wisconsin | t: 920.233.6161 | info@oshkoshdoor.com| **oshkoshdoor.com**