

**GPFSC
5-Ply FSC® Certified
Particleboard Core
No Added Urea-Formaldehyde (NAUF)**



Extra Heavy Duty*	* No Additional Blocking Required
	CARB (California Air Resources Board) Compliant
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 – 2014 (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
Thickness	1-3/4", 2", 2-1/4" • 1-3/8" (max size 1-3/8" 3° X 7° & 6° X 7° pair)
Maximum Sizes	Single 4° x 10° Pairs 8° x 10° (regular or DE pair)
Certified Core	100% FSC® Certified NAUF Particleboard Core with chain of custody certification. Core contains no added urea-formaldehyde. Graded to the ANSI A 208.1, Grade LD-2 specification for door core, the panel has an average density of 32lb. per cubic foot. Core is LEED compliant for credits, MR 4, MR 7 (FSC® Certified wood) and IEQ 4.4
Stiles	Matching veneer or HPL over Structural Composite Lumber (SCL) Standard options: solid wood, painted, PVC, etc. (contact factory for full details)
Rails	Structural Composite Lumber (SCL) Optional: Oversized rails available
Faces	Domestic & exotic veneer species, medium density overlay or .050 HPL
Core Assembly	Stiles & rails securely bonded to core using our state of the art hot press technology.
Face Assembly Adhesive	Faces & crossbands (engineered wood product) hot-pressed to core with Type I glue
Warranty	Interior Use —Life of installation High Gloss Finish/ Exterior Use —No Warranty * See complete warranty for details.
Labeling	20 Minute Rating: 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
Special Details	Machining for template hardware, lights, louvers, Dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching available > Priming for field painting
Acoustic Rating	STC 31 (operable unit) when installed with appropriate gasketing 1-3/4" only
LEED® v3 Credit Assistance	MR 4 Recycled Content —Entire assembly 85% pre-consumer, 0% post-consumer. Core 100% pre-consumer, 0% post-consumer MR 7 Certified Wood > FSC® Certification # SCS-COC-004714 > FSC® License # FSC-C020145 EQ 4.4 Low Emitting Material Content

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.