



<i>Extra Heavy Duty*</i>		<i>* No Additional Blocking Required</i>	
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1		
Thickness	1-3/4", 2", 2-1/4" • 1-3/8" (max size 1-3/8" 3° X 7° & 6° X 7° pair)		
Maximum Sizes	Single 4° x 10°	Pairs 8° x 10° (regular or DE pair)	
Certified Core	100% FSC® Certified NAUF Particleboard Core with chain of custody certification. Core contains no added urea-formaldehyde. Graded to the ANSI A 208.1, Grade LD-2 specification for door core, the panel has an average density of 36lb. per cubic foot.		
Stiles	Matching veneer, HPL or PVC over Structural Composite Lumber (SCL), optional solid wood stiles available		
Rails	Structural Composite Lumber (SCL), optional oversized rails available		
Faces	Domestic & exotic veneer species, medium density overlay or HPL		
Crossband	Engineered wood product		
Core Assembly	Stiles & rails securely bonded to core		
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue		
Warranty	Interior Use - Life of installation High Gloss Finish/ Exterior Use - No Warranty *See complete warranty for details.		
Labeling	20 Minute Rating: 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure		
Special Details	Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating		
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Standard color selections • Custom color matching available • Priming for field painting 		
Acoustic Rating	STC 31 (operable unit) when installed with appropriate gasketing, 1-3/4" only		
Sustainability	<ul style="list-style-type: none"> • LEED v3 Credit: MR Recycled Content (46% pre-consumer, 0% post-consumer) and EQ 4.4 Low Emitting Materials and MR 7 Certified Wood FSC Certification # SCS-COC-004714 and FSC License # FSC-C020145 • LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material and Acoustic Performance • CARB (California Air Resources Board) compliant • TSCA Title VI compliant • Greenguard and Greenguard Gold certification 		

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.