OSHKOSH Door Company

Solutions for Today. Impressions for Life.

# GT
## 5-Ply Structural Composite Lumber Core
## Formaldehyde Free

| *Extra Heavy Duty** | * No Additional Blocking Required<br>CARB (California Air Resources Board) Compliant |
|---|---|
| **Industry Performance Standards** | **WDMA IS.1.A13 & AWS Edition 2 – 2014**<br>(also older version of WDMA, AWI 1300 and WI Section 20 when specified) |
| **Thickness** | 1-IJò 2ò 2-ı ò 1-$^{3}/_{8}$ò (max size 1-$^{3}/_{8}$ò $3^{0}$ X $7^{0}$ & $6^{0}$ X $7^{0}$ pair) |
| **Maximum Sizes** | Single $4^{0}$ x $10^{0}$ Pairs $8^{0}$ x $10^{0}$ (regular or DE pair) |
| **Core** | Structural Composite Lumber (SCL)(38 pcf density). Core contains no added formaldehyde and is **LEED compliant with EQ credit 4.4** |
| **Stiles** | Matching veneer or HPL over Structural Composite Lumber (SCL)<br>Standard options: solid wood, painted, PVC, etc. (contact factory for full details) |
| **Rails** | Structural Composite Lumber (SCL) |
| **Faces** | Domestic & exotic veneer species, medium density overlay or .050 HPL |
| **Core Assembly** | Stiles & rails securely bonded to core using our state of the art hot press technology. |
| **Face Assembly Adhesive** | Faces & crossbands hot-pressed to core with Type I glue |
| **Crossband** | Engineered wood product |
| **Warranty** | **Interior Use**—Life of installation **High Gloss Finish/ Exterior Use**—No Warranty<br>* See complete warranty for details. |
| **Labeling** | **20 Minute Rating:** 1-¾" thick or thicker doors<br>Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure |
| **Special Details** | Machining for template hardware, lights, louvers, Dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations.<br>* Louvers not allowed with 20 minute rating. |
| **Factory Finish** | WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)<br>> Clear > Standard color selections<br>> Custom color matching available > Priming for field painting |
| **LEED® v3 Credit Assistance** | **EQ 4.4 Low Emitting Materials** |

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.