



Solutions for Today. Impressions for Life.

**GTFSC  
5-Ply FSC® Certified  
Structural Composite Lumber Core  
No Added Urea Formaldehyde (NAUF)**

<b>Extra Heavy Duty*</b>		<b>* No Additional Blocking Required</b>	
		<b>CARB (California Air Resources Board) Compliant</b>	
<b>Industry Performance Standards</b>	<b>WDMA IS.1.A13 &amp; AWS Edition 2 – 2014</b> (also older versions of WDMA, AWI 1300 and WI Section 20 when specified)		
<b>Thickness</b>	1-3/4"		
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 10 <sup>0</sup>	Pairs 8 <sup>0</sup> x 10 <sup>0</sup> (regular or DE pair)	
<b>Core</b>	FSC® Certified Structural Composite Lumber (SCL). (38 pcf density) Core is <b>LEED compliant for credits, MR 7</b> (FSC® Certified wood) and <b>IEQ 4.4</b> . (No added formaldehyde)		
<b>Stiles</b>	Matching veneer or HPL over Structural Composite Lumber (SCL) Standard options: solid wood, painted, PVC, etc. (contact factory for full details)		
<b>Rails</b>	Structural Composite Lumber (SCL)		
<b>Faces</b>	Domestic & exotic veneer species, medium density overlay or .050 HPL		
<b>Core Assembly</b>	Stiles & rails securely bonded to core using our state of the art hot press technology.		
<b>Face Assembly Adhesive</b>	Faces & crossbands hot-pressed to core with Type I glue		
<b>Crossband</b>	Engineered wood product		
<b>Warranty</b>	<b>Interior Use</b> —Life of installation	<b>High Gloss Finish/ Exterior Use</b> —No Warranty * See complete warranty for details.	
<b>Labeling</b>	<b>20 Minute Rating:</b> 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure		
<b>Special Details</b>	Machining for template hardware, lights, louvers, Dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating.		
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Custom color matching available > Standard color selections > Priming for field painting		
<b>LEED® v3 Credit Assistance</b>	<b>MR 7 Certified Wood</b> > FSC® Certification # SCS-COC-004714 > FSC® License # FSC-C020145 <b>EQ 4.4 Low Emitting Materials</b>		



Oshkosh Door Company reserves the right to change design and/or details of its products without notice.