

## GW 5-Ply Agrifiber (Wheat) Core No Added Urea-Formaldehyde (NAUF)



<b>Standard Duty*</b> <i>(unblocked)</i>	<b>* Heavy Duty or Extra Heavy Duty with Blocking</b>
	<b>CARB (California Air Resources Board) Compliant</b>
<b>Industry Performance Standards</b>	<b>WDMA IS.1.A13 &amp; AWS Edition 2 – 2014</b> (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
<b>Thickness</b>	1-3/4", 2", 2-1/4" • 1-3/8" (max size 1-3/8" 3 <sup>0</sup> X 7 <sup>0</sup> & 6 <sup>0</sup> X 7 <sup>0</sup> pair)
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 10 <sup>0</sup> Pairs 8 <sup>0</sup> x 10 <sup>0</sup> (regular or DE pair)
<b>Core &amp; STC Rating</b>	Agrifiber board complies with ANSI A208.1 grade 1 – LD- 2 (32 lb.) Core is <b>LEED Compliant, EQ credit 4.4</b> (NAUF), <b>MR 4</b> (Recycled content) & <b>MR 6</b> (rapidly renewable)
<b>Stiles</b>	Matching veneer or HPL over Structural Composite Lumber (SCL) Standard options: solid wood, painted, PVC, etc. (contact factory for full details)
<b>Rails</b>	Structural Composite Lumber (SCL) Optional: Oversized rails available
<b>Faces</b>	Domestic & exotic veneer species, medium density overlay or .050 HPL
<b>Core Assembly</b>	Stiles & rails securely bonded to core using our state of the art hot press technology.
<b>Face Assembly Adhesive</b>	Faces & crossbands (engineered wood product) hot-pressed to core with Type I glue
<b>Warranty</b>	<b>Interior Use</b> —Life of installation <b>High Gloss Finish/ Exterior Use</b> —No Warranty * See complete warranty for details.
<b>Labeling</b>	<b>20 Minute Rating:</b> 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
<b>Special Details</b>	Machining for template hardware, lights, louvers, Dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear      > Standard color selections > Custom color matching available      > Priming for field painting
<b>Acoustic Rating</b>	STC 31 (operable unit) when installed with appropriate gasketing 1-3/4" only
<b>LEED® v3 Credit Assistance</b>	<b>EQ 4.4 Low Emitting Materials</b> <b>MR 4 Recycled Content</b> —Entire assembly 85% pre-consumer, 0% post-consumer. Core 100% pre-consumer, 0% post-consumer <b>MR 6 -- Rapidly Renewable Material</b>

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.