

# OSHKOSH

Door Company

www.oshkoshdoor.com

**QUICK REFERENCE FOR GFP, GPF & GPFSC,  
45 MINUTE LABELED PARTICLE CORE DOORS  
Per UBC 7-2 1997 CATEGORY "A" or "B" Positive Pressure and Negative Pressure**

	Single	Reg. Pair	DE Pair	Notes**
Max. Opening Size 45 min	4-0x8-0	6-0x7-0	N/A	Max leaf size 4-0
Max. Opening Size with Transom (max. transom size 4-0 x 3-4)	N/A	N/A	N/A	
Max. Opening size with Surface Vertical Rods including top rod only	4-0x8-0	6-0x7-0	N/A	
Max. Opening size with labeled concealed vertical rods (less Bottom Rod)	N/A	N/A	N/A	
Concealed Vertical Rods	N/A	N/A	N/A	
Max. Opening size with labeled flush bolts	N/A	6-0x7-0	N/A	Automatic, Manual and surface mounted
Labeled hinges Mortised, Spring or Continuous	Yes	Yes	N/A	
Labeled Latch Sets, including Rim and Mortise Exit Devices (minimum latch bolt throw must be ½")	Yes	Yes	N/A	Max. backset for cylindrical locks 5"
Labeled Dead Bolt	Yes	Yes	N/A	In addition to positive latching device

**NOTE: :** Category "A" doors have the intumescent factory installed in the stile and top rail. No additional intumescent need to be installed on the frame. A listed smoke gasket is required for a "S" label. Category "B" will require a surface applied intumescent applied to the frame and supplied by others.

**PLEASE CONTACT FACTORY FOR COMPLETE DETAILS**

\*\*Options listed, but not limited to, under the Notes column will affect cost. Complete information regarding configuration and hardware, whether surface or mortised, is required for accurate pricing.

**TECHNICAL FACT SHEET 1008-12**

**PAGE \_\_\_ OF \_\_\_**

	Single	Reg. Pair	DE Pair	Notes*
Surface Metal Edge Guards	Yes	Yes	N/A	
Mortised Metal Edge Guards	N/A	N/A	N/A	
Viewer (1" maximum)	Yes	Yes	N/A	
Protection Plates of Brass, Bronze, Steel, Aluminum, Poly Carbonate or PVC types up to 16" high from bottom of door	Yes	Yes	N/A	One or both sides of the door
Fusible Link Louvers	576 sq. in.	576 sq. in.	N/A	Must be located below 40" & can not be used in conjunction with lites or exit hardware
Vision Lights (max size) 45 min	1296 sq. in.	1296 sq. in.	1296 sq. in.	Available with primed metal or veneered metal
Multiple Vision Kits	Yes	Yes	Yes	Total sq. in. can not exceed max shown
Labeled Automatic Door Bottoms	Yes	Yes	N/A	Surface mounted, semi mortised or fully mortised
Race Ways (wire chases)	N/A	N/A	N/A	
Plant-on Moldings	Yes	Yes	Yes	
Electric strikes	N/A	N/A	N/A	
Electric Power Transfer	N/A	N/A	N/A	
Concealed Closer Arms	N/A	N/A	N/A	
Dutch Doors (max. size)	N/A	N/A	N/A	
Acoustical Doors (max. size)	N/A	N/A	N/A	
Lead Lined Doors (max size)	N/A	N/A	N/A	

\*Note: Due to the intricacies and multiple options available, an all-inclusive chart is impossible. For detailed information concerning specific applications, please contact the factory.  
Phone 920-233-6161 or fax to 1-800-782-1281