

www.oshkoshdoor.com

QUICK REFERENCE "CGF" DOORS 45, 60 & 90 MINUTE LABELED FRP DOORS POSITIVE PRESSURE Per UL 10C 2009 CATEGORY "A"

	Single	Reg. Pair	DE Pair	Notes**
Max. Opening Size 45, 60 & 90 min	4-0x8-0	N/A	N/A	
Max. Opening Size with Transom (max. transom size 4-0 x 3-4)	N/A	N/A	N/A	
Max. Opening size with Surface Vertical Rods	4-0x8-0			
Max. Opening size with labeled concealed vertical rods (less Bottom Rod)	N/A	N/A	N/A	
Concealed Vertical Rods	N/A	N/A	N/A	
Max. Opening size with labeled flush bolts	N/A	N/A	N/A	
Labeled hinges Mortised or Continuous	Yes	N/A	N/A	
Labeled Latch Sets, including Rim and Mortise Exit Devices (minimum latch bolt throw must be ½"	Yes	N/A	N/A	Max. backset for locks 2 3/4"
Labeled Dead Bolt	Yes	N/A	N/A	In addition to positive latching device

NOTE: Category "A" doors have the Intumescent factory installed in the stile and top rail. No additional Intumescent need to be installed on the frame. A listed smoke gasket is required for a "S" label.

PLEASE CONTACT FACTORY FOR COMPLETE DETAILS

**Options listed, but not limited to, under the Notes column will affect cost. Complete info	rmation
regarding configuration and hardware, whether surface or mortised, is required for accurate	pricing.

TECHNICAL FACT SHEET 1009-12	PAGE	_ OF
------------------------------	------	------

	Single	Reg. Pair	DE Pair	Notes*
Surface Metal Edge Guards	N/A	N/A	N/A	
Mortised Metal Edge Guards	N/A	N/A	N/A	
Viewer (1" maximum)	Yes	N/A	N/A	
Protection Plates of Brass, Bronze, Steel, Aluminum, Poly Carbonate or PVC types up to 16" high	Yes	N/A	N/A	One or both sides of the door
Fusible Link Louvers	N/A.	N/A.	N/A.	
Vision Lights (max size)	100 sq. in.	N/A	N/A	Primed or painted metal
Multiple Vision Kits	N/A	N/A	N/A	
Labeled Automatic Door Bottoms	Yes	N/A	N/A	Surface mounted only
Race Ways (wire chases)	Yes	N/A	N/A	3/8" by 3/8"
Plant-on Moldings	N/A	N/A	N/A	
Electric strikes	N/A	N/A	N/A	
Electric Power Transfer	N/A	N/A	N/A	
Concealed Closer Arms	N/A	N/A	N/A	
Dutch Doors (max. size)	N/A	N/A	N/A	
Acoustical Doors (max. size)	N/A	N/A	N/A	
Lead Lined Doors (max size)	N/A	N/A	N/A	

*Note: Due to the intricacies and multiple options available, an all-inclusive chart is impossible. For detailed information concerning specific applications, please contact the factory.

Phone 920-233-6161 or fax to 1-800-782-1281

TECHNICAL FACT SHEET	1009-12	PAGE _	_ OF	
----------------------	---------	--------	------	--