

FRP CorGuard CGH Door	This door is specifically designed to withstand high winds and flying debris as well as provide corrosion protection from exposure to water, salt and other harsh chemicals. Hurricane approvals include Florida Building Code (FL12845) and Texas Department of Insurance (Dr390). Design pressure tested to is + or - minus 70 PSF.
Thickness	1 3/4"
Maximum Sizes	4-0 X 7-0 single 6-0 X 7-0 Reg pairs
Core	3 lb density closed cell polystyrene
Stiles	Solid polymer with FRP reinforcement
Rails	Solid Polymer ➤ Bottom rails are oversized to allow for field trimming.
Blocking	Each door comes with two solid polymer lock blocks, mid rail and closer reinforcement.
Faces	.120 thick smooth FRP. (Not available with pebble face)
Core Assembly	Stiles and rails are securely bonded to the core and abrasively planed as an assembly to insure a smooth uniform surface.
Warranty	10 years against defects in workmanship and life of installation against corrosion induced failure. See complete warranty for full details.
Special Details	Machining for templated hinges, cylindrical / mortise locks and rim exit devices. Please contact the factory for full details.
Factory Finish	All doors with smooth surface faces are factory primed as a standard and available with standard and custom matched paint colors.

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.