

<b>FRP CorGuard CGH Door</b>	This door is specifically designed to withstand high winds and flying debris as well as provide corrosion protection from exposure to water, salt and other harsh chemicals. Hurricane approvals include Florida Building Code (FL12845) and Texas Department of Insurance (Dr390). Design pressure tested to is + or - minus 70 PSF.
<b>Thickness</b>	1 3/4"
<b>Maximum Sizes</b>	4-0 X 7-0 single 6-0 X 7-0 Reg pairs
<b>Core</b>	3 lb density closed cell polystyrene
<b>Stiles</b>	Solid polymer with FRP reinforcement
<b>Rails</b>	Solid Polymer ➤ Bottom rails are oversized to allow for field trimming.
<b>Blocking</b>	Each door comes with two solid polymer lock blocks, mid rail and closer reinforcement.
<b>Faces</b>	.120 thick smooth FRP. (Not available with pebble face)
<b>Core Assembly</b>	Stiles and rails are securely bonded to the core and abrasively planed as an assembly to insure a smooth uniform surface.
<b>Warranty</b>	10 years against defects in workmanship and life of installation against corrosion induced failure. See complete warranty for full details.
<b>Special Details</b>	Machining for templated hinges, cylindrical / mortise locks and rim exit devices. Please contact the factory for full details.
<b>Factory Finish</b>	All doors with smooth surface faces are factory primed as a standard and available with standard and custom matched paint colors. Smooth paint finish is low semi-gloss (40-45).

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.