

# OSHKOSH

Door Company

www.oshkoshdoor.com

## QUICK REFERENCE 20 MINUTE LABELED DOORS POSITIVE PRESSURE Per UBC 7-2 1997 CATEGORY "B"

	Single	Reg. Pair	DE Pair	Notes*
Max. Opening Size (max. leaf 4-0 wide)	4-0x9-0	8-0x9-0	N/A	
Max. Opening Size with Transom (max. transom size 4-0 x 3-4)	N/A	N/A	N/A	
Max. Opening size with Surface Vertical Rods	4-0x9-0	8-0x9-0	N/A	Pairs furnished with or without metal edges and / or astragal.
Max. Opening size with labeled concealed vertical rods	4-0x9-0	8-0x9-0	N/A	Requires 5" primed or veneered metal edges
Max. Opening size with labeled flush bolts	N/A	8-0x9-0	N/A	Pairs can be furnished with or without metal edges and or astragal.
Labeled hinges Mortised, Spring or Continuous	Yes	Yes	Yes	
Labeled Latch Sets, including Rim and Mortise Exit Devices (minimum latch bolt throw must be 1/2")	Yes	Yes	Yes	Max. backset for cylindrical locks 5"
Labeled Dead Bolt	Yes	Yes	Yes	In addition to positive latching device

**NOTE:** Category "B" doors **OPTION 1** must be installed with a UBC 7-2 1997 listed Intumescent seal either applied to the door or frame per the instructions of the Intumescent seal manufacturer. For "S" label requirements a listed smoke gasket must also be installed. **OPTION 2 No Intumescent seals required at the outer perimeter of single or paired openings when doors installed with Pemko S88 gaskets. Also provides "S" label. Pemko HSS2000 required at meeting edges of pairs.**

**Note: Surface applied Intumescent, gaskets and or seals are not supplied by Oshkosh.**

**PLEASE CONTACT FACTORY FOR COMPLETE DETAILS**

\*Note: Options listed, but not limited to, under the Notes column will affect cost. Complete information regarding configuration and hardware, whether surface or mortised, is required for accurate pricing.

**TECHNICAL FACT SHEET 1006-08**

**PAGE \_\_\_ OF \_\_\_ 31**

	Single	Reg. Pair	DE Pair	Notes*
Surface Metal Edge Guards	Yes	Yes	Yes	
Mortised Metal Edge Guards	N/A	N/A	N/A	
Viewer (1" maximum)	Yes	Yes	Yes	
Protection Plates of Brass, Bronze, Steel, Aluminum, Poly Carbonate or PVC types up to 48" high	Yes	Yes	Yes	One or both sides of the door
Louvers	N/A	N/A	N/A	
Vision Lights (max size)	1296 sq. in.	1296 sq. in.	1296 sq. in.	Available with primed metal, veneered metal and wood vision kits
Multiple Vision Kits	Yes	Yes	Yes	Total sq. in. can not exceed 1296
Labeled Automatic Door Bottoms	Yes	Yes	Yes	Surface mounted, semi mortised or fully mortised
Race Ways (wire chases)	Yes	Yes	Yes	
Plant-on Moldings	Yes	Yes	Yes	1" Max thickness and 1 3/4" max width
Electric strikes	N/A	Yes	N/A	
Electric Power Transfer	Yes	Yes	Yes	
Concealed Closer Arms	N/A	N/A	N/A	
Dutch Doors (max. size)	N/A	N/A	N/A	
Acoustical Doors (max. size)	N/A	N/A	N/A	Flush only
Lead Lined Doors (max size)	4-0x8-0	N/A	N/A	

Note: Due to the intricacies and multiple options available, an all-inclusive chart is impossible. For detailed information concerning specific applications, please contact the factory. Procedures are subject to change and or modification without notice.

Phone 920-233-6161 or fax to 1-800-782-1281

**TECHNICAL FACT SHEET**

**1006-08**

**Page**      **of**