

CGFRF FRP CorGuard 45, 60 or 90 min PP Door Frame (Fiberglass Reinforced Polymer)

FRP CorGuard CGFRF Fire Rated Door Frame Positive Pressure	This door frame is specifically designed for use in harsh environments where fire ratings are required. The FRP and polymer construction is ideal for any project where the doors are frequently exposed to water, salt and other harsh chemicals. Can only be installed in masonry wall applications.
Jamb Depths	5 3/4" only
Maximum Sizes	4-0x8-0 single
Style	Masonry profile. Standard construction is knock down for field assembly. Jamb sections and head bar are secured together by interlocking FRP angles and stainless steel screws. Options for chemically welding the frame together as a complete assembly are also available.
Anchors	Standard frame designed for use with "T" strap anchors. Optional anchoring configuration of punch and dimple for bolt in masonry is also available.
Reinforcements	All reinforcements and component parts are FRP, solid polymer or fire retardant material.
Head Bars	2" face only.
Transom Bars & Mullions	Not allowed.
Lights	Not allowed.
Warranty	10 years against defects in workmanship and life of installation against corrosion induced failure. See complete warranty for full details.
Special Details	Machining for templated hardware Please contact the factory for full details.
Factory Finish	All frames are factory primed as a standard and available with standard and custom matched paint colors.

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.