

GFP45 5-Ply Particle Core 45 Minute



<i>Extra Heavy Duty*</i>		<i>* No Additional Blocking Required</i>	
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1		
Thickness	1 3/4"		
Maximum Sizes	4° x 8° single and 6° x 7° std pairs (no DE)		
Core	Particleboard complies with ANSI A208.1 grade 1 – LD- 2 (38 lb.)		
Stiles	Matching veneer or HPL over composite fire rated material		
Rails	Composite fire rated material		
Faces	Domestic and exotic veneer species, medium density overlay or HPL		
Crossband	Engineered wood product		
Core Assembly	Stiles and rails bonded to core		
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue		
Warranty	Interior Use - Life of installation High Gloss Finish/ Exterior Use - No Warranty *See complete warranty for details.		
Labeling	45 Min. 1 3/4" thick doors. Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure		
Special Details	Machining for templated hardware, lights, louvers and applied moldings. Refer to specific technical sheets for details and limitations.		
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Custom color matching available • Standard color selections • Priming for field painting 		
Sustainability	<ul style="list-style-type: none"> • LEED v3 Credit: MR Recycled Content (46% pre-consumer, 0% post-consumer) • LEED v4 Credit: MR Sourcing and EPD • CARB (California Air Resources Board) compliant • TSCA Title VI compliant • Greenguard and Greenguard Gold certification 		

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.