

**SOUND RETARDANT DOOR**  
**Sound Transmission class (STC) 32**  
**Formaldehyde Free**

**OSHKOSH**  
Door Company

**GFA32**

CARB (California Air Resources Board) compliant

**SPECIFICATIONS**

**Industry Performance Standards**

**WDMA IS.1.A11 & AWS -09**

(also older versions of WDMA, AWI 1300 and WI section 20 when specified)

**Maximum sizes**

4-0 X 10-0 single

**Thickness**

1 3/4"

**Core**

Special acoustical materials IEQ 4.4 (no added formaldehyde)

**Stiles**

Matching veneer or HPL over composite fire rated material

**Top & Bottom Rails**

Fire retardant composite

**Core Assembly**

Stiles and rails bonded to core

**Face Assembly / Adhesive**

Faces & crossbands hot-pressed to core with Type I glue

**Crossband**

Engineered wood product

**Faces**

Domestic and exotic veneer species, medium density overlay or .050 HPL

**Labeling**

45 - 90 Min. singles doors. Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative Pressure

**Special Details**

Check with factory for machining options

**Factory Finish**

UV finish in standard & custom match colors meeting or exceeding AWI system 9 and WDMA TR6. Priming for field painting also available.

**Acoustic Rating**

STC32 (operable unit) When installed with appropriate gasketing

**Gasketing**

**Set 13:** See detail drawing sheet **DD613** for gaskets and installation of

**Warranty**

Full Door Warranty for Life of Installation on interior applications. *Warranty does not cover exterior applications or the appearance of high gloss finishes or field finishes. See complete warranty for details.*

**Visit us at [www.oshkoshdoor.com](http://www.oshkoshdoor.com)**

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

**OSHKOSH**  
Door Company

For more information call: **920-233-6161**

Date: 8/13

Product Data Sheet: 630