

**GA35**  
**Sound Retardant Door**  
**Sound Transmission Class (STC) 35**  
**No Added Urea-Formaldehyde (NAUF)**

CARB (California Air Resources Board) Compliant	
Industry Performance Standards	<b>WDMA IS.1.A13 &amp; AWS Edition 2 – 2014</b> (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
Thickness	1 – 3/4”
Maximum Sizes	4’ x 8’ single using as pairs will reduce STC rating
Core	Special Acoustical Materials <b>EQ 4.4</b>
Stiles	Matching veneer or HPL over Structural Composite Lumber (SCL) Standard Options: solid wood, painted, PVC, etc. (contact factory for full details)
Rails	Mill option hardwood or SCL (FRP doors have polymer)
Faces	Domestic & exotic veneer species, medium density overlay, .050 HPL or FRP
Core Assembly	Stiles & rails securely bonded to core using our state of the art hot press technology.
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue.
Crossband	Engineered Wood Product (not required with FRP faces)
Warranty	<b>Interior Use</b> —Life of installation <b>High Gloss Finish/ Exterior Use</b> —No Warranty * See complete warranty for details.
Labeling	20 minute single doors. Subject to ASTM E-152 and Interek Testing Services (Warnock Hersey) Negative or Positive Pressure Category “B” Not available with FRP Face
Special Details	Special blocking, applied mouldings, Dutch doors, pairs and some hardware preps may affect the STC rating * Vision kits available up to 864 sq. inches in non-labeled doors
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching available > Priming for field painting
Acoustical Rating	<b>STC35</b> (operable unit) when installed with appropriate gasketing
Gasketing	<b>Set 11:</b> See detail drawing sheet <b>DD611</b> for gaskets & installation

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.