



Solutions for Today. Impressions for Life.

**GA42  
Sound Retardant Door  
Sound Transmission Class (STC) 42  
No Added Urea-Formaldehyde (NAUF)**

<b>CARB (California Air Resources Board) Complaint</b>	
<b>Industry Performance Standards</b>	<b>WDMA IS.1.A13 &amp; AWS Edition 2 – 2014</b> (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
<b>Thickness</b>	1 – 3/4”
<b>Maximum Sizes</b>	4 <sup>0</sup> x 8 <sup>0</sup> single using as pairs will reduce STC rating
<b>Core</b>	Special acoustical materials <b>EQ 4.4</b> <span style="float: right;">RCGP <b>NAUF</b></span>
<b>Stiles</b>	Matching veneer or HPL over Structural Composite Lumber (SCL) Options: > Solid wood    > Painted    > PVC    > Contact Factory for Full Details
<b>Rails</b>	Mill option hardwood or SCL (FRP Doors have polymer)
<b>Faces</b>	Domestic & exotic veneer species, medium density overlay, .050 HPL, or FRP
<b>Core Assembly</b>	Stiles & rails securely bonded to core using our state of the art hot press technology.
<b>Face Assembly Adhesive</b>	Faces & crossbands hot-pressed to core with Type I glue.
<b>Crossband</b>	Engineered Wood Product (Not required with FRP faces)
<b>Warranty</b>	<b>Interior Use</b> —Life of installation <b>High Gloss Finish/ Exterior Use</b> —No Warranty * See complete warranty for details.
<b>Labeling</b>	20 minute single doors. Subject to ASTM E-152 and Interek Testing Services (Warnock Hersey) Negative or Positive Pressure Category “B” . > Not available with FRP Face
<b>Special Details</b>	Special blocking, applied moldings, dutch doors, pairs, special hardware preps and vision kits may affect the STC Rating.
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear    > Standard color selections > Custom color matching available    > Priming for field painting
<b>Vision Kit</b>	At 20 minute 100 sq in of 5/16” ceramic or 484 sq in of Pyrostop At non-labeled 484 sq in of 1/2” laminated
<b>Acoustical Rating</b>	<b>STC42</b> (operable unit) when installed with appropriate gasketing
<b>Gasketing</b>	Customer option <b>Gasket Set 15 or 18</b> detail drawings DD615 & DD618. See detail drawing sheets for gasket types and installation
<b>LEED® v3 Credit Assistance</b>	<b>EQ 4.4 Low Emitting Material Content</b>

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.