

Right product. Right place. Right time.

## **GLL** Lead Lined -- Optional constructions can comply with FSC® Certified or No Added Urea-Formaldehyde (NAUF)

Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1
Thickness	1-34"
Maximum Sizes	Single 4° x 8° Pairs 8° x 8°
Core	Particleboard core (LSL available for additional charge) non-rated and 20 minute doors. 100% FSC® Certified NAUF Particleboard Core with chain of custody certification. Core can be LEED compliant for MR 7, and EQ 4.4 (NAUF). Fire rated composite material for 45 and 60-minute doors.
Stiles	Matching veneer or HPL over mill option hardwood or composite stiles
Rails	Structural Composite Lumber Composite fire rated material at 45 or 60 minute
Faces	Domestic & exotic veneer species, medium density overlay or .050 HPL
Core Assembly	Stiles & rails securely bonded to core.
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue.
Lead	$^{1}/_{32}$ " to $^{1}/_{8}$ "
Warranty	Interior Use—Life of installation   * See complete warranty for details.   High Gloss Finish/ Exterior Use—No Warranty
Labeling	20, 45, and 60 Minute Rating Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure.
Special Details	Machining for templated hardware, lights, and applied moldings.
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)  > Clear  > Standard color selections  > Custom color matching available  > Priming for field painting
LEED® v3 Credit Assistance	MR 7 Certified Wood > FSC® Certification # SCS-COC-004714 > FSC® License # FSC-C020145 EQ 4.4 Low Emitting Material Content

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.