

GPF 5-Ply Particleboard Core No Added Urea Formaldehyde (NAUF)



Extra Heavy Duty*		*No additional blocking required
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 – 2019 (also older version of WDMA, AWI 1300 and WI Section 20 when specified)	
Thickness	1-3/4", 2", 2-1/4" and 1-3/8" (max size 1-3/8" 3'0" x 7'0" & 6'0" x 7'0" pair)	
Maximum Sizes	Single 4'0" x 10'0"	Pairs 8'0" x 10'0" (regular or DE pair)
Core	100% No-Added Urea-Formaldehyde Particleboard conforming to ANSI A 208.1, Grade LD-2 requirements 32lb. density.	
Stiles	Matching veneer or HPL over Structural Composite Lumber (SCL) Optional solid wood, painted, or PVC edges available	
Rails	Structural Composite Lumber (SCL), Optional: Oversized rails available	
Faces	Domestic & exotic veneer species, medium density overlay or HPL	
Crossband	Engineered wood product	
Core Assembly	Stiles & rails securely bonded to core using hot press technology.	
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue	
Warranty	Interior Use - Life of installation *See complete warranty for details.	High Gloss Finish/ Exterior Use - No Warranty
Labeling	20 Minute 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure	
Special Details	Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating	
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Custom color matching available • Standard color selections • Priming for field painting 	
Acoustic Rating	STC 31 (operable unit) when installed with appropriate gasketing, 1-3/4" only	
Sustainability	<ul style="list-style-type: none"> • LEED v3 Credit: MR Recycled Content (46% pre-consumer, 0% post-consumer) and EQ 4.4 Low Emitting Materials • LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material, and Acoustic Performance • CARB (California Air Resources Board) compliant • TSCA Title VI compliant • Greenguard and Greenguard Gold certification 	

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.