



| <i>Extra Heavy Duty*</i> | | <i>* No Additional Blocking Required</i> | |
|---------------------------------------|---|--|--|
| Industry Performance Standards | WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1 | | |
| Thickness | 1-3/4", 2", 2-1/4" • 1-3/8" (max size 1-3/8" 3° X 7° & 6° X 7° pair) | | |
| Maximum Sizes | Single 4° x 10° | Pairs 8° x 10° (regular or DE pair) | |
| Certified Core | 100% FSC® Certified NAUF Particleboard Core with chain of custody certification. Core contains no added urea-formaldehyde. Graded to the ANSI A 208.1, Grade LD-2 specification for door core, the panel has an average density of 36lb. per cubic foot. | | |
| Stiles | Matching veneer, HPL or PVC over Structural Composite Lumber (SCL), optional solid wood stiles available | | |
| Rails | Structural Composite Lumber (SCL), optional oversized rails available | | |
| Faces | Domestic & exotic veneer species, MDO, HPL and 3-ply HDF & HPL | | |
| Crossband | Engineered wood product | | |
| Core Assembly | Stiles & rails securely bonded to core | | |
| Face Assembly Adhesive | Faces & crossbands hot-pressed to core with Type I glue | | |
| Warranty | Interior Use - Life of installation High Gloss Finish/ Exterior Use - No Warranty *See complete warranty for details. | | |
| Labeling | 20 Minute Rating: 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure | | |
| Special Details | Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating | | |
| Factory Finish | WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Standard color selections • Custom color matching available • Priming for field painting | | |
| Acoustic Rating | STC 31 (operable unit) when installed with appropriate gasketing, 1-3/4" only | | |
| Sustainability | <ul style="list-style-type: none"> • LEED v3 Credit: MR Recycled Content (46% pre-consumer, 0% post-consumer) and EQ 4.4 Low Emitting Materials and MR 7 Certified Wood FSC Certification # SCS-COC-004714 and FSC License # FSC-C020145 • LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material and Acoustic Performance • CARB (California Air Resources Board) compliant • TSCA Title VI compliant • Greenguard and Greenguard Gold certification | | |

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.