

GSFSC 5-Ply FSC ® Certified Stave Lumber Core No Added Urea-Formaldehyde (NAUF)

| Extra Heavy Duty* | * No Additional Blocking Required |
|--|--|
| | CARB (California Air Resources Board) Compliant |
| Industry Performance Standards | WDMA IS.1.A13 & AWS Edition 2 – 2014 (also older version of WDMA, AWI 1300 and WI Section 20 when specified) |
| Thickness | 1-3/4" |
| Maximum Sizes | Single 4° x 8° Standard Pairs 6° x 7° (no double egress) |
| Core | 100% FSC® Certified NAUF Particleboard Core with chain of custody certification (38 lbs.) Core is LEED compliant for MR 7, and EQ 4.4 (NAUF). |
| Stiles | Matching veneer or HPL over composite fire rated material |
| Rails | Structural Composite Lumber |
| Faces | Domestic & exotic veneer species, medium density overlay or .050 HPL |
| Core Assembly | Stiles & rails securely bonded to core using our state of the art hot press technology. |
| Face Assembly Adhesive | Faces & crossbands (engineered wood product) hot-pressed to core with Type I glue. |
| Warranty | Interior Use—Life of installation High Gloss Finish/ Exterior Use—No Warranty * See complete warranty for details. |
| Labeling | 20 Minute Rating: 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure. |
| Special Details | Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating |
| Factory Finish | WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching available > Priming for field painting |
| LEED [®] v3 Credit Assistance | MR 7 Certified Wood > FSC® Certification # SCS-COC-004714 > FSC® License # FSC-C020145 EQ 4.4 Low Emitting Material Content |

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.