

GTFSC
5-Ply FSC® Certified
Structural Composite Lumber Core
No Added Urea Formaldehyde (NAUF)

Extra Heavy Duty*

*** No Additional Blocking Required**

Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 – 2019 (also older versions of WDMA, AWI 1300 and WI Section 20 when specified)
Thickness	1-3/4", 2", 2-1/4" 1-3/8" (max size 1-3/8" 3'0" X 7'0" & 6'0" X 7'0" pair)
Maximum Sizes	Single 4'0" x 10'0" Pairs 8'0" x 10'0" (regular or DE pair)
Core	FSC® Certified Structural Composite Lumber (SCL). (38 pcf density) (No added formaldehyde)
Stiles	Matching veneer, HPL or PVC over Structural Composite Lumber (SCL), Optional solid wood stiles available
Rails	Structural Composite Lumber (SCL)
Faces	Domestic & exotic veneer species, medium density overlay or HPL
Crossband	Engineered wood product
Core Assembly	Stiles & rails securely bonded to core using hot press technology.
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue
Warranty	Interior Use - Life of installation High Gloss Finish/ Exterior Use - No Warranty *See complete warranty for details.
Labeling	20 Minute Rating: 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
Special Details	Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating.
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Standard color selections • Custom color macting available • Priming for field painting
Sustainability	<ul style="list-style-type: none"> • LEED v3 Credit: MR 7 Certified Wood FSC Certification # SCS-COC-004714 and FSC License # FSC-C020145 and EQ 4.4 Low Emitting Materials • LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material • CARB (California Air Resources Board) compliant, ULEF • TSCA Title VI compliant • Greenguard and Greenguard Gold certification



Oshkosh Door Company reserves the right to change design and/or details of its products without notice.