

**GTFSC**  
**5-Ply FSC® Certified**  
**Structural Composite Lumber Core**  
**No Added Urea Formaldehyde (NAUF)**

<i>Extra Heavy Duty*</i>		* No Additional Blocking Required
<b>Industry Performance Standards</b>	WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1	
<b>Thickness</b>	1-3/4", 2", 2-1/4" 1-3/8" (max size 1-3/8" 3'0" X 7'0" & 6'0" X 7'0" pair)	
<b>Maximum Sizes</b>	Single 4'0" x 10'0"	Pairs 8'0" x 10'0" (regular or DE pair)
<b>Core</b>	FSC® Certified Structural Composite Lumber (SCL). (38 pcf density) (No added formaldehyde)	
<b>Stiles</b>	Matching veneer, HPL or PVC over Structural Composite Lumber (SCL), Optional solid wood stiles available	
<b>Rails</b>	Structural Composite Lumber (SCL)	
<b>Faces</b>	Domestic & exotic veneer species, MDO, HPL and 3-ply HDF & HPL	
<b>Crossband</b>	Engineered wood product	
<b>Core Assembly</b>	Stiles & rails securely bonded to core	
<b>Face Assembly Adhesive</b>	Faces & crossbands hot-pressed to core with Type I glue	
<b>Warranty</b>	Interior Use - Life of installation High Gloss Finish/ Exterior Use - No Warranty *See complete <a href="#">warranty</a> for details.	
<b>Labeling</b>	20 Minute Rating: 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure	
<b>Special Details</b>	Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating.	
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> <li>• Clear</li> <li>• Standard color selections</li> <li>• Custom color macting available</li> <li>• Priming for field painting</li> </ul>	
<b>Sustainability</b>	<ul style="list-style-type: none"> <li>• LEED v3 Credit: MR 7 Certified Wood FSC Certification # SCS-COC-004714 and FSC License # FSC-C020145 and EQ 4.4 Low Emitting Materials</li> <li>• LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material</li> <li>• CARB (California Air Resources Board) compliant, ULEF</li> <li>• TSCA Title VI compliant</li> <li>• Greenguard and Greenguard Gold certification</li> </ul>	



Oshkosh Door Company reserves the right to change design and/or details of its products without notice.