

PRODUCT DATA SHEET

Maximum Sizes, Non-Rated	Single 4-0 x 10-0, Paired 8-0 x 10-0
Maximum Sizes, 20 Minute Rated	Single 4-0 x 9-0, Paired 8-0 x 9-0
Maximum Size, 45, 60, & 90 Minute Rated	Single 4-0 x 8-0, Paired 8-0 x 8-0
Thickness	3/4" non-rated & 20 minute flat jambs & T-stop jambs. 1 1/8" non-rated & 20 minute single & double rabbet jambs. 7/8" 45, 60, & 90 minute flat jambs & T-stop jambs. 1 1/2" 45, 60 & 90 minute single rabbet jambs
Jamb Width	Any standard wall thickness is available up to 8 3/4". Premium charges apply for widths over 8 3/4". 3 3/4" minimum for 20 minute. 4 3/4" minimum for 45, 60 minute. 5" minimum for 90 minute.
Core	Non-rated & 20 minute solid lumber core (NO FINGER JOINTED PRODUCTS). The 45, 60, and 90 minute core is a patented fire rated composition.
Species	Any commercially available lumber for non-rated jambs. Our 20 minute jambs must have a hardness density of (33.4PCF) Our 45, 60, and 90 minute jambs are available in any commercially available wood veneer.
Labeling	20, 45, 60, & 90 minute for single & paired openings per approvals by Intertek Testing Service (Warnock Hersey).
Factory Finish	Clear coat, standard or custom match colors. Prime coat for paint grade.
Neutral / Positive Pressure	All of our jambs meet neutral pressure & positive pressure requirements.
Item Identification	Each jamb set is labeled for their own opening per your schedule.
Jamb Profiles	T-stop, flat, single & double rabbet.
Casing	Standard is our ODC-208 3/4" x 2 1/2" flat with radius edges. Other options available upon request.
Borrowed Lights & Transoms	Available for non-rated applications only.
Custom Options	Custom manufacturing is available. Please send us your request for quote.
SOS Shipments	Limited availability, contact factory.
Warranty	Full jamb warranty for the life of the installation on interior applications. Warranty does not cover exterior use or appearance of high gloss finish or field finishes.

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.