

Right product. Right place. Right time.

CGF FRP CorGuard 45-90 min Fire Core Door (Fiberglass Reinforced Polymer)

FRP CorGuard CGS Door	This door is specifically designed for use in harsh environments. The FRP and polymer construction is ideal for any project where the doors are frequently exposed to water, salt and other harsh chemicals. Also, due to its completely sealed and smooth surfaces on all six sides it is an ideal option for hospitals and laboratories.
Thickness	1 3/4"
Maximum Sizes	4-0 X8-0 single
Core	Fire rated material
Stiles	Fire rated composite material with polymer outer edge
Rails	Fire rated composite material with polymer outer edge
Blocking	Each door comes with a fire rated composite lock block. Optional blocking is available for closers and other surface mounted hardware.
Faces	Standard faces are .090 thick smooth FRP. Options are available for .120 thick faces as well as FRP pebble faces both in .090 and .120.
Core Assembly	Stiles and rails are securely bonded to the core and abrasively planed as an assembly to insure a smooth uniform surface.
Warranty	10 years against defects in workmanship and life of installation against corrosion induced failure. See complete warranty for full details. (Fire rated doors not warranted for exterior use)
Special Details	Machining for templated "C" & "M" locks, mortised and continuous hinges, Exit devices (not concealed), raceways, viewers, other listed surface mounted hardware and metal vision kits up to 100 sq. inches. Contact the factory for complete listing.
Factory Finish	All doors with smooth surface faces are factory primed as a standard and available with standard and custom matched paint colors. Smooth paint finish is low semi-gloss (40-45). Pebble faced doors are available with standard or optional custom match colors. Fire rated pebble faced doors are only available with smooth stiles painted to harmonize with the face.

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.