

COR-GUARD

Fire Rated 45-90 min

FRP DOOR (Fiberglass Reinforced Polymer)

OSHKOSH
Door Company

CGF

SPECIFICATIONS

Cor-Guard CGF door	This door is specifically designed for use in harsh environments. The FRP and polymer construction is ideal for any project where the doors are frequently exposed to water, salt and other harsh chemicals. Also due to its completely sealed and smooth surfaces all six sides it is an ideal option for hospitals and laboratory clean rooms.
Maximum sizes	4-0 X 8-0 single
Thickness	1 3/4"
Core	Fire rated material
Stiles	Fire rated composite
Top & Bottom Rails	Fire rated composite
Blocking	Each door comes with a fire rated composite lock block Optional blocking is available for closers and other surface mounted hardware
Core Assembly	Stiles and rails are securely bonded to core
Door Faces	Standard faces are .090 thick smooth FRP Optional .120 thick smooth faces are available
Special Details	Machining for templated "C" & "M" locks, Dead locks, Std hinges & continous Exit devices (not concealed), Viewer, contact factory for complete listing Listed surface mounted hardware and metal vision kits to 100 sq inches
Finishes	Primed for field painting and standard paint colors Optional custom paint color matching available
Warranty	10 years interior only See complete Warranty for full details

Visit us at:

WWW.Cor-Guard.com or Oshkoshdoor.com

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.

OSHKOSH
Door Company

For more information call: **920-233-6161**

Date: 7/12

Product Data Sheet: TFS103