

GFAPB 60 5-Ply Agri Fiber Composite Core No Added Urea Formaldehyde (NAUF)

Standard* <i>(unblocked)</i>	* Heavy Duty or Extra Heavy Duty w/ Blocking	
Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 – 2019 (also older version of WDMA, AWI 1300 and WI Section 20 when specified)	
Thickness	1-3/4"	
Maximum Sizes	Single 4 ⁰ x 8 ⁰	Pairs Not Available
Core	Agri fiber Particleboard (28-32 pcf density). Core is NAUF	
Stiles	Matching veneer, HPL, or PVC over Composite Fire Rated Mineral	
Rails	Composite fire rated mineral, optional oversized rails available	
Faces	Domestic & exotic veneer species, medium density overlay or HPL	
Crossband	Engineered wood product	
Core Assembly	Stiles & rails securely bonded to core using hot press technology.	
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue	
Warranty	Interior Use - Life of installation * See complete warranty for details.	High Gloss Finish/ Exterior Use—No Warranty
Labeling	60 Minute Rating: In Singles only Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure	
Special Details	Machining for template hardware, no lites allowed, 24x24 max louver size & applied moldings. Refer to specific technical sheets for details and limitations.	
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Custom color matching available • Standard color selections • Priming for field painting 	
Sustainability	<ul style="list-style-type: none"> • Leed v3 Credit: EQ 4.4 Low emitting materials MR4: recycled content (core 90% pre consumer, 0% post consumer) • Leed v4 Credit: MR: EPD, Sourcing of raw materials, EQ: low emitting materials • CARB (California Air Resources Board) Compliant • TSCA Title VI Compliant • Greenguard & Greenguard Gold Certification 	



Oshkosh Door Company reserves the right to change design and/or details of its products without notice.