

GFSCCL 5-Ply Structural Composite Lumber Core No Added Urea Formaldehyde (NAUF)

*Extra Heavy Duty**

* No Additional Blocking Required

Industry Performance Standards	WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1	
Thickness	1-3/4"	
Maximum Sizes	Single 4 ⁰ x 10 ⁰	Pairs 8 ⁰ x 8 ⁰ regular or DE
Core	Fire Treated Structural Composite Lumber SCL(39 pcf density). Core is NAUF	
Stiles	Matching veneer, HPL, or PVC over Structural Composite Lumber (SCL) or Composite Fire Rated Mineral	
Rails	Structural Composite Lumber (SCL) or Composite Fire Rated Mineral	
Faces	Domestic & exotic veneer species, medium density overlay or HPL	
Crossband	Engineered wood product	
Core Assembly	Stiles & rails securely bonded to core	
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue	
Warranty	Interior Use - Life of installation	High Gloss Finish/ Exterior Use - No Warranty
Labeling	45 Minute Rating: In Singles and Pairs Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure	
Special Details	Machining for template hardware, 30x36 max light size, 24x24 max louver size, & applied moldings. Refer to specific technical sheets for details and limitations.	
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)	
	<ul style="list-style-type: none"> • Clear • Custom color matching available 	<ul style="list-style-type: none"> • Standard color selections • Priming for field painting
Sustainability	<ul style="list-style-type: none"> • Leed v3 Credit: EQ 4.4 Low emitting materials • Leed v4 Credit: MR: EPD, Sourcing of raw materials, EQ: low emitting materials • CARB (California Air Resources Board) Compliant • TSCA Title VI Compliant • Greenguard & Greenguard Gold Certification 	

