

GFSCCL 5-Ply Structural Composite Lumber Core No Added Urea Formaldehyde (NAUF)

*Extra Heavy Duty**

** No Additional Blocking Required*

| | | |
|---------------------------------------|---|--|
| Industry Performance Standards | WDMA IS.1.A13 & AWS Edition 2 – 2019 (also older version of WDMA, AWI 1300 and WI Section 20 when specified) | |
| Thickness | 1-3/4" | |
| Maximum Sizes | Single 4 ⁰ x 10 ⁰ | Pairs 8 ⁰ x 8 ⁰ regular or DE |
| Core | Fire Treated Structural Composite Lumber SCL(39 pcf density). Core is NAUF | |
| Stiles | Matching veneer, HPL, or PVC over Structural Composite Lumber (SCL) or Composite Fire Rated Mineral | |
| Rails | Structural Composite Lumber (SCL) or Composite Fire Rated Mineral | |
| Faces | Domestic & exotic veneer species, medium density overlay or HPL | |
| Crossband | Engineered wood product | |
| Core Assembly | Stiles & rails securely bonded to core using hot press technology. | |
| Face Assembly Adhesive | Faces & crossbands hot-pressed to core with Type I glue | |
| Warranty | Interior Use - Life of installation | High Gloss Finish/ Exterior Use - No Warranty *See complete warranty for details. |
| Labeling | 45 Minute Rating: In Singles and Pairs Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure | |
| Special Details | Machining for template hardware, 30x36 max light size, 24x24 max louver size, & applied moldings. Refer to specific technical sheets for details and limitations. | |
| Factory Finish | WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Custom color matching available • Standard color selections • Priming for field painting | |
| Sustainability | <ul style="list-style-type: none"> • Leed v3 Credit: EQ 4.4 Low emitting materials • Leed v4 Credit: MR: EPD, Sourcing of raw materials, EQ: low emitting materials • CARB (California Air Resources Board) Compliant • TSCA Title VI Compliant • Greenguard & Greenguard Gold Certification | |

