

51P^m Agri Fiber

A e r e F r e e A F

Standard	Available or extra available w/ locking
(unblocked)	
Y T C E A Q U E F E C E F H A B A C E Y U A O a a c a [] A G A . A G E F J	<input checked="" type="checkbox"/> (also older version of WDMA, AWI 1300 and WI Section 20 when specified)
1-3/4"	<input type="checkbox"/>
Single 4⁰ x 10⁰	<input type="checkbox"/> Úæá:•ÁÌ ÈÌ ÇÁÌ ÈÌ ÈÌ* ~ æ:ÁÌ [:ÁÖÖÁ
Core Assembly	Core is NAUF
Matching veneer, HPL, or PVC over Structural Composite Lumber (SCL) or Composite Fire Rated Mineral	
Rails	Structural Composite Lumber (SCL) or Composite Fire Rated Mineral
Faces	Domestic & exotic veneer species, medium density overlay or HPL
Engineered wood product	
Core Assembly	Stiles & rails securely bonded to core using hot press technology.
Faces & crossbands hot-pressed to core with Type I glue	
Life of installation	Pá* @ÁÖ [[••ÁÖá] á• @DÁÖçç^:á [:ÁW•^ÁÉÁN No Warranty *See complete warranty for details.
In Singles and Pairs	Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)	
Clear	• Standard color selections
Custom color matching available	• Priming for field painting
Sustainability	<p>~ Š^ááçHÁÖ:ÁááçKÁÖÜÁ I É I Á Š [, Á^ { áccá } *Á { æç^:áæ } •</p> <p>~ Š^ááç I Á Ö:ÁááçKÁ T Ü K Á Ö Ü Ö É Á Ü [~ I & á } *Á [-Á:æ , Á { æç^:áæ } • É Á Ö Ü K Á [, Á^ { áccá } *Á { æç^:áæ } •</p> <p>~ Ö Ç E Ü Ö Á Ç Ö æ æ - [:] ; æ Á Ç E : Á Ü ^ • [~ I & ^ Á Ö [æ : á D Á Ö [{] æ } c</p> <p>~ V Ü Ö Ç E Á V ä c ^ Á X Ö Á Ö [{] æ } c</p> <p>~ Ö : ^ ^ } * ~ æ : á Á B Á Ö : ^ ^ } * ~ æ : á Á Ö [á Á Ö ^ : c i - i & æ c á []</p>



Oshkosh Door Company reserves the right to change design and/or details of its products without notice.