

GFAPB 45 5-Ply Agri Fiber Composite Core No Added Urea Formaldehyde (NAUF)

Standard* (unblocked)

* Heavy Duty or Extra Heavy Duty w/ Blocking

Industry Performance Standards WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1

Thickness 1-3/4"

Maximum Sizes Single 4⁰ x 10⁰ Pairs 8⁰ x 8⁰ regular or DE

Core Agri fiber Particleboard (28-32 pcf density). Core is NAUF

Stiles Matching veneer, HPL, or PVC over Structural Composite Lumber (SCL) or Composite Fire Rated Mineral

Rails Structural Composite Lumber (SCL) or Composite Fire Rated Mineral

Faces Domestic & exotic veneer species, medium density overlay or HPL

Crossband Engineered wood product

Core Assembly Stiles & rails securely bonded to core

Face Assembly Adhesive Faces & crossbands hot-pressed to core with Type I glue

Warranty Interior Use - Life of installation High Gloss Finish/ Exterior Use - No Warranty
*See complete [warranty](#) for details.

Labeling 45 Minute Rating: In Singles and Pairs
Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure

Special Details Machining for template hardware, max light dimensions 1296 sq in, 36" wide, 54" height. 24x24 max louver size & applied moldings. Refer to specific [technical sheets](#) for details and limitations.

Factory Finish WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)

- Clear
- Custom color matching available
- Standard color selections
- Priming for field painting

Sustainability

- Leed v3 Credit: EQ 4.4 Low emitting materials
- Leed v4 Credit: MR: EPD, Sourcing of raw materials, EQ: low emitting materials
- CARB (California Air Resources Board) Compliant
- TSCA Title VI Compliant
- Greenguard & Greenguard Gold Certification

