

GFAPB 45 5-Ply Agri Fiber Composite Core No Added Urea Formaldehyde (NAUF)

Standard* <i>(unblocked)</i>	* Heavy Duty or Extra Heavy Duty w/ Blocking	
Industry Performance Standards	WDMA I.S.1A-2021AWS Edition 2 (rev. 2019), (WI)NAAWS 4.0	
Thickness	1-3/4"	
Maximum Sizes	Single 4 ⁰ x 10 ⁰	Pairs 8 ⁰ x 8 ⁰ regular or DE
Core	Agri fiber Particleboard (28-32 pcf density). Core is NAUF	
Stiles	Matching veneer, HPL, or PVC over Structural Composite Lumber (SCL) or Composite Fire Rated Mineral	
Rails	Structural Composite Lumber (SCL) or Composite Fire Rated Mineral	
Faces	Domestic & exotic veneer species, medium density overlay or HPL	
Crossband	Engineered wood product	
Core Assembly	Stiles & rails securely bonded to core	
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue	
Warranty	Interior Use - Life of installation	High Gloss Finish/ Exterior Use - No Warranty *See complete warranty for details.
Labeling	45 Minute Rating: In Singles and Pairs Subject to ASTM E2074 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure	
Special Details	Machining for template hardware, max light dimensions 1296 sq in, 36" wide, 54" height. 24x24 max louver size & applied moldings. Refer to specific technical sheets for details and limitations.	
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> • Clear • Custom color matching available • Standard color selections • Priming for field painting 	
Sustainability	LEED v4 Credit: MR Credit, EPD, EQ Credit low Emitting Material, Greenguard and Greenguard Gold Certificate. CARB (California Air Resources Board) compliant, NAUF, TSCA Title VI Compliant , Greenguard and Greenguard Gold Certification	



Oshkosh Door Company reserves the right to change design and/or details of its products without notice.