

Right product. Right place. Right time.

GFAPB 60 5-Ply Agri Fiber Composite Core No Added Urea Formaldehyde (NAUF)



Standard* (unblocked)	* Heavy Duty or Extra Heavy Duty w/ Blocking
Industry Performance Standards	WDMA I.S.1A-2021 & AWS Edition 2 (rev. 2019), (WI) NAAWS 4.0
Thickness	1-3/4"
Maximum Sizes	Single 4 ⁰ x 8 ⁰ Pairs Not Available
Core	Agri fiber Particleboard (28-32 pcf density). Core is NAUF
Stiles	Matching veneer, HPL, or PVC over Composite Fire Rated Mineral
Rails	Composite fire rated mineral, optional oversized rails available
Faces	Domestic & exotic veneer species, medium density overlay or HPL
Crossband	Engineered wood product
Core Assembly	Stiles & rails securely bonded to core
Face Assembly Adhesive	Faces & crossbands hot-pressed to core with Type I glue
Warranty	Interior Use - Life of installation High Gloss Finish/ Exterior Use—No Warranty * See complete warranty for details.
Labeling	60 Minute Rating: In Singles only Subject to ASTM E2074and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
Special Details	Machining for template hardware, no lites allowed, 24x24 max louver size & applied moldings. Refer to specific technical sheets for details and limitations.
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) • Clear • Standard color selections • Custom color matching available • Priming for field painting
Sustainability	 LEED v4 Credit: MR Credit, EPD, EQ Credit low Emitting Material, Greenguard and Greenguard Gold Certificate. CARB (California Air Resources Board) compliant, NAUF, TSCA Title VI Compliant, Greenguard and Greenguard Gold Certification

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.