

## GFSCCL 5-Ply Structural Composite Lumber Core No Added Urea Formaldehyde (NAUF)

**Extra Heavy Duty\***

**\* No Additional Blocking Required**

<b>Industry Performance Standards</b>	WDMA I.S. 1A-2021 & AWS Edition 2 (rev. 2019), (WI) NAAWS 4.0
<b>Thickness</b>	1-3/4"
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 10 <sup>0</sup> Pairs 8 <sup>0</sup> x 8 <sup>0</sup> regular or DE
<b>Core</b>	Fire Treated Structural Composite Lumber SCL(39 pcf density). Core is NAUF
<b>Stiles</b>	Matching veneer, HPL, or PVC over Structural Composite Lumber (SCL) or Composite Fire Rated Mineral
<b>Rails</b>	Structural Composite Lumber (SCL) or Composite Fire Rated Mineral
<b>Faces</b>	Domestic & exotic veneer species, medium density overlay or HPL
<b>Crossband</b>	Engineered wood product
<b>Core Assembly</b>	Stiles & rails securely bonded to core
<b>Face Assembly Adhesive</b>	Faces & crossbands hot-pressed to core with Type I glue
<b>Warranty</b>	Interior Use - Life of installation      High Gloss Finish/ Exterior Use - No Warranty *See complete <a href="#">warranty</a> for details.
<b>Labeling</b>	45 Minute Rating: In Singles and Pairs Subject to ASTM E2074 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
<b>Special Details</b>	Machining for template hardware, 30x36 max light size, 24x24 max louver size, & applied moldings. Refer to specific <a href="#">technical sheets</a> for details and limitations.
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> <li>• Clear</li> <li>• Standard color selections</li> <li>• Custom color matching available</li> <li>• Priming for field painting</li> </ul>
<b>Sustainability</b>	LEED v4 Credit: MR Credit, EPD, EQ Credit low Emitting Material, Greenguard and Greenguard Gold Certificate and Acoustic Performance. CARB (California Air Resources Board) compliant, NAUF, TSCA Title VI Compliant, Greenguard and Greenguard Gold Certification

