

**GLL**  
**Lead Lined -- Optional constructions can comply with FSC<sup>®</sup> Certified. No Added Urea-Formaldehyde (NAUF)**

|                                       |   |                                       |
|---------------------------------------|---|---------------------------------------|
| <b>Industry Performance Standards</b> | WDMA I.S. 1A-2021 & AWS Edition 2 (rev. 2019), (WI) NAAWS 4.0   |                                       |
| <b>Thickness</b>                      | 1-3/4"  |                                       |
| <b>Maximum Sizes</b>                  | Single 4 <sup>0</sup> x 8 <sup>0</sup>  | Pairs 8 <sup>0</sup> x 8 <sup>0</sup> |
| <b>Core</b>                           | Particleboard core (LSL available for additional charge) non-rated and 20 minute doors. Fire rated composite material for 45 and 60-minute doors.                     |                                       |
| <b>Stiles</b>                         | Matching veneer or HPL over mill option hardwood or composite stiles  |                                       |
| <b>Rails</b>                          | Structural Composite Lumber<br>Composite fire rated material at 45 or 60 minute   |                                       |
| <b>Faces</b>                          | Domestic & exotic veneer species, medium density overlay or .050 HPL  |                                       |
| <b>Core Assembly</b>                  | Stiles & rails securely bonded to core.   |                                       |
| <b>Face Assembly Adhesive</b>         | Faces & crossbands hot-pressed to core with Type I glue.  |                                       |
| <b>Lead</b>                           | 1/32" to 1/8"   |                                       |
| <b>Warranty</b>                       | <b>Interior Use</b> —Life of installation <b>High Gloss Finish/ Exterior Use</b> —No Warranty<br>* See complete <a href="#">warranty</a> for details.                 |                                       |
| <b>Labeling</b>                       | <b>20, 45, and 60 Minute Rating</b><br>Subject to ASTM E2074 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure.                            |                                       |
| <b>Special Details</b>                | Machining for templated hardware, lights, and applied moldings.   |                                       |
| <b>Factory Finish</b>                 | WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)<br>> Clear > Standard color selections<br>> Custom color matching available > Priming for field painting     |                                       |
| <b>Sustainability</b>                 | LEED v4 Credit: Credit low Emitting Material, Greenguard and GreenGold Certificate<br>CARB (California Air Resources Board Compliant, NAUF, TSCA Title VI compliant). |                                       |

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.