

*Extra Heavy Duty\**

\* No Additional Blocking Required



<b>Industry Performance Standards</b>	WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1
<b>Thickness</b>	1-3/4", 2", 2-1/4" • 1-3/8" (max size 1-3/8" 3 <sup>0</sup> X 7 <sup>0</sup> & 6 <sup>0</sup> X 7 <sup>0</sup> pair)
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 10 <sup>0</sup> Pairs 8 <sup>0</sup> x 10 <sup>0</sup> (regular or DE pair)
<b>Certified Core</b>	100% FSC® Certified NAUF Particleboard Core with chain of custody certification. Core contains no added urea-formaldehyde. Graded to the ANSI A 208.1, Grade LD-2 specification for door core, the panel has an average density of 34lb. per cubic foot.
<b>Stiles</b>	Matching veneer, HPL or PVC over Structural Composite Lumber (SCL), optional solid wood stiles available
<b>Rails</b>	Structural Composite Lumber (SCL), optional oversized rails available
<b>Faces</b>	Domestic & exotic veneer species, MDO, HPL and 3-ply HDF
<b>Crossband</b>	Engineered wood product
<b>Core Assembly</b>	Stiles & rails securely bonded to core
<b>Face Assembly Adhesive</b>	Faces & crossbands hot-pressed to core with Type I glue
<b>Warranty</b>	Interior Use - Life of installation      High Gloss Finish/ Exterior Use - No Warranty *See complete <a href="#">warranty</a> for details.
<b>Labeling</b>	20 Minute Rating: 1-3/4" thick or thicker doors Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure
<b>Special Details</b>	Machining for template hardware, lights, louvers, dutch doors, special blocking, & applied moldings. Refer to specific technical sheets for details and limitations. * Louvers not allowed with 20 minute rating
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> <li>• Clear</li> <li>• Standard color selections</li> <li>• Custom color matching available</li> <li>• Priming for field painting</li> </ul>
<b>Acoustic Rating</b>	STC 31 (operable unit) when installed with appropriate gasketing, 1-3/4" only
<b>Sustainability</b>	<ul style="list-style-type: none"> <li>• LEED v3 Credit: MR Recycled Content (46% pre-consumer, 0% post-consumer) and EQ 4.4 Low Emitting Materials and MR 7 Certified Wood FSC Certification # SCS-COC-004714 and FSC License # FSC-C020145</li> <li>• LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material and Acoustic Performance</li> <li>• CARB (California Air Resources Board) compliant</li> <li>• TSCA Title VI compliant</li> <li>• Greenguard and Greenguard Gold certification</li> </ul>

Oshkosh Door Company reserves the right to change design and/or details of its products without notice.