



Right product. Right place. Right time.

**GFSCCL45**  
**5-Ply FSC® Certified**  
**Structural Composite Lumber Core**  
**No Added Urea Formaldehyde (NAUF)**

|                                       |   |  |  |
|---------------------------------------|---|--|--|
| <b>Extra Heavy Duty*</b>              |   | <b>* No Additional Blocking Required</b>   |  |
| <b>Industry Performance Standards</b> | WDMA IS.1.A13 & AWS Edition 2 (rev. 2019), (WI)NAAWS 3.1  |  |  |
| <b>Thickness</b>                      | 1-3/4"  |  |  |
| <b>Maximum Sizes</b>                  | Single 4 <sup>0</sup> x 10 <sup>0</sup>   | Pairs 8 <sup>0</sup> x 8 <sup>0</sup> (regular or DE pair)   |  |
| <b>Core</b>                           | FSC® Certified Structural Composite Lumber(SCL). (39 pcf density) (No added urea formaldehyde)  |  |  |
| <b>Stiles</b>                         | Matching veneer, HPL or PVC over Structural Composite Lumber (SCL), or Composite Fire Rated Mineral   |  |  |
| <b>Rails</b>                          | Structural Composite Lumber (SCL) or Composite Fire Rated Mineral   |  |  |
| <b>Faces</b>                          | Domestic & exotic veneer species, MDO, HPL  |  |  |
| <b>Crossband</b>                      | Engineered wood product   |  |  |
| <b>Core Assembly</b>                  | Stiles & Rails securely bonded to core  |  |  |
| <b>Face Assembly Adhesive</b>         | Faces & crossbands hot-pressed to core with Type I glue   |  |  |
| <b>Warranty</b>                       | Interior Use - Life of installation   | High Gloss Finish/ Exterior Use - No Warranty<br>*See complete <a href="#">warranty</a> for details. |  |
| <b>Labeling</b>                       | 45 Minute Rating: 1-3/4" thick<br>Subject to ASTM E-152 and Intertek Testing Services (Warnock Hersey) Negative or Positive Pressure  |  |  |
| <b>Special Details</b>                | Machining for template hardware, 30 x 36 max light size, 24 x 24 max louver size, & applied moldings. Refer to specific technical sheets for details and limitations.   |  |  |
| <b>Factory Finish</b>                 | WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) <ul style="list-style-type: none"> <li>• Clear</li> <li>• Standard color selections</li> <li>• Custom color macting available</li> <li>• Priming for field painting</li> </ul>   |  |  |
| <b>Sustainability</b>                 | <ul style="list-style-type: none"> <li>• LEED v3 Credit: MR 7 Certified Wood FSC Certification # SCS-COC-004714 and FSC License # FSC-C020145 and EQ 4.4 Low Emitting Materials</li> <li>• LEED v4 Credit: MR Sourcing and EPD, EQ Low Emitting Material</li> <li>• CARB (California Air Resources Board) compliant, ULEF</li> <li>• TSCA Title VI compliant</li> <li>• Greenguard and Greenguard Gold certification</li> </ul> |  |  |



Oshkosh Door Company reserves the right to change design and/or details of its products without notice.